



### O-Ring Dichtungen

NW	Silikon taubenblau +180 / -50° C FDA	EPDM schwarz +125 / -40° C FDA	Viton schwarz +200 / -10° C
	Artikel Nr.	Artikel Nr.	Artikel Nr.
100	201si	201ep	201vi
150	215si	215ep	215vi
200	220si	220ep	220vi
250	225si	225ep	225vi
300	230si	230ep	230vi
350	235si	235ep	235vi
400	240si	240ep	240vi
450	245si	245ep	245vi
500	250si	250ep	250vi
600	260si	260ep	260vi
700	270si	270ep	270vi
800	280si	280ep	280vi
900	290si	290ep	290vi
1000	210si	210ep	210vi

### nahtlos ummantelte FEP-/PFA O-Ringe

NW	FEP-Silikon FEP-ummantelt +204 / -60° C Mantel: transparent Kern: rot FDA	FEP-Viton FEP-ummantelt +204 / -20° C Mantel: transparent Kern: schwarz FDA	PFA-Silikon PFA-ummantelt +260 / -60° C Mantel: transparent Kern: rot FDA
	Artikel Nr.	Artikel Nr.	Artikel Nr.
100	201fes	201fev	201pfa
150	215fes	215fev	215pfa
200	220fes	220fev	220pfa
250	225fes	225fev	225pfa
300	230fes	230fev	230pfa
350	235fes	235fev	235pfa
400	240fes	240fev	240pfa
450	245fes	245fev	245pfa
500	250fes	250fev	250pfa
600	260fes	260fev	260pfa
700	270fes	270fev	270pfa
800	280fes	280fev	280pfa
900	290fes	290fev	290pfa
1000	210fes	210fev	210pfa